| Index Terms | <u>L</u> | <u>inks</u> |
|------------------------------------|----------|-------------|
| Accelerometers, microminiature | 475 | |
| Actuators | | |
| centrifugal force | 225 | |
| for control of tension and speed | 348 | |
| inchworm (piezoelectric) | 172 | |
| linear, AC and DC | 21 | |
| mechanical | 5 | 425 |
| microactuators | 475 | |
| rotary | 31 | |
| rotary, cartridge-operator | 130 | |
| shaft, air-spring | 186 | |
| solenoid-type | 31 | |
| stepper motor-based | 21 | |
| Adjusters | | |
| cam-motion | 156 | |
| linkage-motion | 156 | |
| valve-stroke | 156 | |
| Adjusting devices | 196 | |
| Adjustments, fine-focus | 286 | |
| Air springs | | |
| bellows-type | 186 | |
| rolling-diaphragm type | 187 | |
| vehicle-suspension type | 187 | |
| Amplifiers | | |
| impulse | 340 | |
| mechanical power | | |
| applications | 221 | |
| capstan-type | 221 | |
| windlass | 223 | |
| motor, (servomotor), electronic | | |
| linear | 8 | |
| pulse-width modulated (PWM) | 8 | |
| Arrangements | | |
| cam-and-gear, for warning | 341 | |
| cam-and-linkage | 340 | |
| contact, switch, relay, electrical | 360 | |
| gear-shift | 282 | |
| weight-regulating | 55 | |
| | | |
| Ball | | |
| bushing | 129 | |
| cartridge | 128 | |
| screws | 2 | 12 |
| slides | 2 | 128 |
| Ballistic particle manufacturing | | |
| (BPM), (SeeRapid Prototyping) | | |
| Bands | | |
| spiral clutch | 307 | |
| spring | 307 | |
| taut | 185 | |
| Bearings | | |
| air | 5 | |
| ball | 260 | |
| | | |

| <u>Index Terms</u> | <u>L</u> i | <u>inks</u> | | | |
|------------------------------------|------------|-------------|-----|-----|-----|
| Bearing, cont. | | | | | |
| commercial | 10 | 129 | | | |
| eccentrically bored | 299 | | | | |
| elastometric | 289 | | | | |
| linear roller | 197 | | | | |
| reciprocating, ball | 129 | | | | |
| sleeve | 129 | | | | |
| Bellcrank | 147 | | | | |
| Bellows | | | | | |
| general | 6 | 308 | | | |
| pressure sensing | 183 | 365 | 382 | 394 | 397 |
| temperature sensing | 394 | 395 | | | |
| Belts | | | | | |
| bead chain | 228 | 229 | | | |
| cable-chain hybrid | 230 | | | | |
| flat | 227 | | | | |
| flexible | 342 | | | | |
| hybrid | 227 | | | | |
| ladder chain, cable and plastic | 230 | | | | |
| tensioning | 231 | | | | |
| timing | 227 | 228 | 230 | | |
| with four-bar linkage | 95 | | | | |
| variable speed with chain | 224 | | | | |
| V- | 227 | | | | |
| wound helix wire | 55 | | | | |
| Bimetal elements and sensors | 392 | 396 | | | |
| Bolt nut | 5 | | | | |
| Brakes | | | | | |
| automatic hoist | 408 | | | | |
| band | 336 | | | | |
| caliper (disk) | 340 | | | | |
| clutches/brake systems | 304 | 326 | 336 | 340 | |
| clutch, double-coil | 327 | | | | |
| electromagnetic with clutches with | 326 | | | | |
| foot-controlled system | 378 | | | | |
| reel, permanent magnet | 387 | | | | |
| slip | 304 | 327 | | | |
| variable-torque drag | 306 | | | | |
| Bushings, torsion | 300 | | | | |
| | | | | | |
| Cams | | | | | |
| basics | 200 | | | | |
| barrel | 202 | 207 | 209 | | |
| circular | 201 | | | | |
| circular-arc | 204 | 205 | | | |
| computer emulation of | 4 | | | | |
| conical | 159 | | | | |
| constant-velocity | 201 | | | | |
| control | 94 | | | | |
| cut-out | 154 | | | | |
| cycloid, cycloidal motion in | 203 | | | | |
| cylindrical | 200 | | | | |
| double-faced | 154 | | | | |
| | | | | | |

| <u>Index Terms</u> | <u>L</u> | inks |
|--|------------|---------|
| Cams cont. | | |
| double-revolution | 209 | |
| drives, for machine tools | 210 | |
| dwell | | |
| adjustable | 209 | |
| compensating for | 204 | |
| quick-acting | 209 | |
| eccentric | 313 | |
| floating, quick-acting | 209 | |
| general use | 319 | 341 |
| generating curves for | 201 | |
| groove | 125 | |
| indexing | 209 | |
| jaws, in hydraulic cylinder | 411 | |
| locking | 104 | |
| lug, adjustable | 210 | |
| mechanisms | 207 | |
| pivot-point, adjustable | 210 | |
| plate, increased-stroke | 209 | |
| radial | 200 | 205 |
| reciprocal, (reciprocating) | 159 | 207 |
| roller position, adjustable | 210 | |
| simple harmonic | 202 | • • • • |
| sliding | 154 | 208 |
| slot | 208 | |
| special-function | 209 | |
| steel ball | 208 | |
| straight-sided | 317 | |
| swash-plate | 208 | |
| three-dimensional | 159 | |
| vibratory motion | 207 | |
| Capstan | 221 | |
| Cells | 202 | |
| load | 382 | |
| Peaucelliers's | 431 | |
| photo | 384 | |
| Chains | 220 | |
| bead | 229 | |
| drives (See Drives) | 227 | |
| gears, with | 227 | |
| length changes | 231 | |
| positive, infinitely variable (PIV) drive roller | 226 | |
| | 222 | |
| bushed | 232 | |
| double | 226 | |
| single Chamical machanical nalishing (CMP) | 226 | 102 |
| Chemical mechanical polishing (CMP) | 478 | 483 |
| Chucks, spring-loaded | 424 | |
| Clamps | 104 | |
| air spring | 186 415 | |
| center-support differential | _ | |
| | 195 414 | |
| double, for spindle head | 414 | |

| Index Terms | <u>Links</u> |
|---------------------------------|--------------|
| Clamps cont. | |
| hold-down | 175 |
| friction | 414 |
| magnetic, permanent | 388 |
| piezoelectric | 45 |
| pedestal | 415 |
| quick-acting | 412 |
| right-angle | 415 |
| slide | 414 |
| specimen holder | 415 |
| spring | 424 |
| table | 415 |
| turntable | 414 |
| Clutches | |
| adjustable | 155 |
| backstopping | 320 |
| band | |
| inside | 336 |
| outside | 336 |
| new-spiral | 307 |
| bidirectional | 308 |
| cam and roller | 303 |
| centrifugal | 309 364 |
| cone | 302 342 |
| design of | 305 |
| detent | 308 |
| dog, one-way | 311 |
| dual-spring slip | 304 |
| duplex, single- and double-coil | 327 |
| driving | 321 |
| eddy current | 326 |
| electrostatic | 327 |
| expanding-shoe | 303 |
| expanding shoe, centrifugal | 303 |
| fixed-field | 326 |
| free-wheeling | 317 |
| friction | 317 |
| general | 302 |
| magnetic | 326 |
| multiple-disk | 323 |
| single-plate | 323 |
| hysterisis | 326 |
| inchworm actuator | 172 |
| jaw | 302 |
| lawnmower | 311 |
| | 326 |
| magnetic friction | |
| | 326 |
| particle-and-fluid | 327 327 |
| magnetostrictive mechanical | 327 |
| | 202 |
| basic | 302 |
| small, for precise service | 322 |
| mercury-gland | 303 |
| | |

| <u>Index Terms</u> | <u>L</u> | <u>inks</u> | | |
|-------------------------------------|----------|-------------|-----|-----|
| Clutches cont. | | | | |
| multidisk | 317 | | | |
| multistation | 325 | | | |
| one-way | 312 | | | |
| overload relief | 323 | | | |
| overriding | 316 | | | |
| overrunning | 285 | 311 | 318 | 320 |
| pawl and ratchet | | | | |
| general | 302 | | | |
| single-cycle, Dennis | 322 | | | |
| single-cycle, dual control | 322 | | | |
| planetary transmission | 302 | 322 | | |
| plates | 302 | 346 | | |
| roller | | | | |
| general | 307 | 312 | | |
| locking, bidirectional | 328 | | | |
| trip | 328 | | | |
| rotating-field | 326 | | | |
| shifting mechanism for | 284 | 286 | | |
| sprag-type | 307 | 311 | 312 | 320 |
| spring | | | | |
| basic | 314 | | | |
| controlled | 306 | | | |
| dual | 304 | | | |
| slip | 304 | | | |
| spring-wrapped | 303 | | | |
| stepped | 305 | | | |
| spring and ball radial detent | 303 | | | |
| station, one and/or two | 324 | 325 | | |
| wedging ball or roller | 52. | 0_0 | | |
| external | 311 | | | |
| internal | 311 | | | |
| Commutation (See Motor commutation) | 311 | | | |
| Computer-aided design (CAD) | | | | |
| drafting, 2D software | 464 | | | |
| glossary of terms | 467 | | | |
| modeling, 3D software | 107 | | | |
| feature-based solid | 466 | | | |
| hybrid surface and solid | 467 | | | |
| solid | 466 | | | |
| wireframe and surface | 465 | | | |
| preparation for rapid prototyping | 468 | | | |
| software improvements | 464 | | | |
| Computer-aided engineering (CAE) | 465 | | | |
| Computer-aided manufacturing (CAM) | 465 | | | |
| Connections (CAM) | 403 | | | |
| | 205 | | | |
| parallel·link | 295 | 410 | | |
| splined Controls | 367 | 418 | | |
| | 209 | | | |
| automatic weighing and filling | 398 | | | |
| carton sorting | 398 | 24 | 10 | |
| closed-loop | 2 | 34 | 43 | |

| <u>Index Terms</u> | <u>Li</u> | nks | | | |
|--|-----------|-----|-----|-----|-----|
| Controls cont. | | | | | |
| fine-focus | 286 | | | | |
| gas range | 394 | | | | |
| hydraulic winch | 222 | | | | |
| inspection, photoelectric | 399 | | | | |
| motion | 2 | | | | |
| open-loop | 2 | 4 | | | |
| photoelectric | 64 | 84 | 398 | | |
| position-loop | 2 | | | | |
| refrigerator | 395 | | | | |
| room-temperature, heavy-duty | 395 | | | | |
| sequencing | | | | | |
| sheet-cutting | 340 | | | | |
| techniques | | | | | |
| derivative | 4 | | | | |
| intregral | 4 | | | | |
| proportional | 4 | | | | |
| proportional-integral derivative (PID) | 4 | | | | |
| tension | 352 | | | | |
| speed, and | 348 | 383 | | | |
| thermostatic | 393 | | | | |
| torque-loop | 2 | | | | |
| velocity (speed) loop | 2 | | | | |
| Controllers | | | | | |
| actuators with | 348 | 351 | 400 | | |
| differential | 351 | | | | |
| float-switch | 400 | | | | |
| indicators, with | 400 | | | | |
| level-controller, switch-actuated | 401 | | | | |
| liquid level | | | | | |
| electrical | 400 | | | | |
| magnetic | 401 | | | | |
| motion | 2 | 4 | 6 | 8 | |
| on-and-off | 348 | | | | |
| programmable logic, (PLC) | 2 | | | | |
| proportioning | 348 | | | | |
| proportioning-throttling | 349 | | | | |
| Coordinate system, six-degree-of-freedom | 2 | | | | |
| Conversion (Converters) | | | | | |
| rotary-to-linear motion | 100 | 130 | 229 | | |
| rotary-to-oscillatory | 229 | | | | |
| torque | | | | | |
| Constantino | 259 | | | | |
| MEMS | 479 | | | | |
| Conveyors | 68 | 237 | 240 | 320 | 399 |
| Coordinate system, six degree of freedom | 2 | | | | |
| Coulisse | 108 | | | | |
| Counters | | | | | |
| electronic, high-speed | 384 | | | | |
| magazine | 384 | | | | |
| pulse | 365 | | | | |
| Couplings (couplers) | | | | | |
| bellows | 6 | | | | |
| | - | | | | |

| <u>Index Terms</u> | <u>Links</u> | |
|------------------------------------|----------------|-----|
| Couplings (couplers) cont. | 221 | |
| Bendix-Weiss | 331 | |
| bent-pin | 337 | |
| Bossler, design of | 298 | |
| constant-velocity joint | 331 | |
| crossed-axis yoke disk-and link | 294 | |
| | 295 | |
| drive-shaft, flexible | 297 | |
| eight-joint | 308 | |
| flexible shaft | 331 | |
| fluid four-bar | 145 345 206 | |
| | | |
| four-link | 300 | |
| grooved-sphere joint | 330 | |
| Hooke's joint | 297 304 330 | |
| instrument, PM | 387 | |
| light-duty | 331 | |
| mechanisms, special for | 337 | |
| misalignment cancelling | 299 | |
| offset shaft | 295 | |
| Oldham | 294 | 225 |
| parallel link | 151 295 308 | 337 |
| parallel shaft | 295 | |
| pin-and-slot | 338 | |
| pinned-sleeve | 330 | |
| pinned-sphere shaft | 330 | |
| pipe-joint | 308 | |
| power transmission | 300 | |
| pump-type | 331 | |
| rotating shafts, methods for | 332 | |
| Rzeppa | 331 | |
| Schmidt | 296 | |
| six-disk | 337 | |
| slip-spring | 311 | |
| space-frame | 297 | |
| spring-plunger | 345 | |
| square-plate | 298 | |
| steel-shot | 345 | |
| three-plate rectangular | 298 | |
| Twiflex | 300 | |
| universal | 297 | |
| Cranks | | |
| double parallel | 430 | |
| fixed | 432 | |
| gear-oscillating | 116 | |
| gear-slider | 116 | |
| input | 432 | |
| nonparallel | 430 | |
| output | 432 | |
| parallel, four bar | 430 | |
| reciprocating-space | 117 | |
| rotating | 431 | |
| slide, 3D | 169 | |
| | | |

| <u>Index Terms</u> | <u>Links</u> |
|---|--------------|
| Cranks cont. | |
| space | 170 |
| spherical | 167 |
| | |
| Detectors, jam | 399 |
| Detents | |
| axial | 417 |
| magnetic | 417 |
| Detents cont. | |
| positive | 416 417 |
| radial | 417 |
| stopping movement for | 94 416 |
| roller | 417 |
| Devices | |
| adjustable | |
| pitch | 115 |
| speed | 115 |
| spacecrank | 115 |
| adjusting | 196 |
| anti-backlash | 319 |
| cartridge-actuated | 402 |
| clamping | 56 414 422 |
| clamping and cutting | 56 |
| cushioning | 175 |
| differential transformer sensing | 382 |
| elliptical-gear planetary | 115 |
| expanding and contracting | 134 |
| four-bar cutter | 56 |
| friction for intermediate rotary motion | 122 123 |
| gaging and calipering | 383 |
| geared cocking | 214 |
| latch, toggle and trigger | 213 |
| orienting | 213 |
| cone-shaped parts | 53 |
| dish-like parts | 52 |
| - | |
| pointed-end parts | 52 52 |
| short, tubular parts | |
| stepped-disk parts | 53 |
| U-shaped parts | 53 |
| pyrotechnic, power | 402 234 |
| rack-and-pinion | |
| rotary-to-reciprocating | 92 114 |
| in-line reciprocator | 114 |
| track-switching scotch yoke | 114 |
| rotation-to-translation | 191 |
| scotch-yoke | 202 |
| screw | 191 |
| self-locking | 192 |
| simple feeding | 53 |
| snap-action | 217 |
| sorting | 54 |
| speed control for mechanisms | 366 |
| tension control | 383 387 |

| <u>Index Terms</u> | <u>L</u> | <u>inks</u> |
|--|----------|-------------|
| Devices cont. | •00 | |
| tilting | 208 | |
| time-delay switching | 130 | |
| toggle | 213 | |
| translation-to-rotation | 192 | |
| variable-speed | 115 | |
| weight-regulating | 55 | |
| warning, boom overload | 341 | |
| Diaphragms | | |
| capsules, with, applications of | 380 | |
| differential pressure | 382 | |
| Differentials | | |
| bevel-gear | 159 | |
| planetary-gear | 163 | |
| rotating-link | 159 | |
| sliding-link | 159 | |
| spiderless | 285 | |
| Diffusion | 476 | |
| Directed-light fabrication (DLF) | | |
| (See Rapid Prototyping) | | |
| Direction changes, straight-line | 142 | |
| Direct-shell production casting (DSPC) | | |
| (See Rapid Prototyping) | | |
| Disconnector, quick | 403 | |
| Disks | | |
| friction | 343 | |
| encoder | 22 | |
| absolute | 23 | |
| incremental | 22 | |
| Sellers' | 254 | |
| spring-mounted | 175 | |
| Drawings, 3D | 464 | |
| Driller, parallel-link | 151 | |
| Drives (drivers) | | |
| adjustable | | |
| chain | 155 | |
| clutch | 155 | |
| cone | 245 | |
| harmonic | 113 | |
| pivot | 155 | |
| slider | 155 | |
| angle-doubling | 152 | |
| angular-momentum-balanced, robot | 48 | |
| ball-and-cone | 250 | |
| ball-and-disk, and | 251 | |
| ball-and-screw | 5 | 12 |
| bearings and roller | 117 | 12 |
| belt | 117 | 224 257 |
| belt-and-chain, variable speed | 224 | 44 4J/ |
| cam for machine tools | 210 | |
| for tool-slide mechanism | 210 | |
| | | |
| two-directional rack-and-gear | 210 | |

| <u>Index Terms</u> | <u>Lin</u> | ks |
|----------------------------|------------|-------------|
| Drives (drivers) cont. | | |
| chain | | |
| adjustable | 155 | |
| double-roller | 226 | |
| general | | 226 234 353 |
| ladder, differential | 229 | |
| oscillating | 118 | |
| for reducing pulsations in | 238 | |
| single-roller | 226 | |
| slider | 118 | |
| with chain | 118 | |
| clutch | 110 | |
| adjustable | 155 | |
| double-spring | | 314 |
| spring, double | 314 | ,,, |
| comb,electrostatic | | 484 |
| cone | 470 | 707 |
| adjustable | 245 | |
| ball, and | 250 | |
| belt | 245 | |
| general | _ | 254 257 |
| Graham | 246 | 234 237 |
| | 245 | |
| electrically-coupled | 246 | |
| planetary | 246 | |
| ring, and roller, and | 257 | |
| | 245 | |
| two curve-slider | 121 | |
| differential | 121 | |
| | 270 | |
| fixed | 270 | |
| general | 352 | |
| robot | 48 | |
| disk | 245 | |
| adjustable | 247 | 257 |
| and roller | | 256 |
| ball, and | 251 | 257 |
| general | | 256 |
| planetary | 247 | |
| spring-loaded | 247 | |
| double | 202 | |
| clutch . | 282 | |
| eccentric | 206 | |
| impulse | 319 | |
| ring | 248 | |
| shift | 282 | |
| sphere | 249 | |
| spring clutch | 314 | |
| toggle-puncher | 153 | |
| drum and roller | 257 | |
| electrical | 352 | |
| electrostatic comb | 476 | |
| epicycloids, (cycloid) | | |
| equations for | 442 | |
| | | |

| <u>Index Terms</u> | Links |
|---|-------------|
| Drives (drivers), epicycloids, (cycloid) cont | |
| reciprocator | 113 |
| elliptical-motion | 113 |
| elliptical-slide | 171 |
| fast-reversal reel | 310 |
| flowmeter | 389 |
| Ford tractor | 273 |
| friction | 142 143 256 |
| full-wave rectifier | 314 |
| gear | |
| compound spur-bevel | 273 |
| oscillating crank | 121 |
| rack | 153 |
| robot | 48 |
| sector | 152 |
| slider crank | 121 |
| wobble | 274 |
| geneva, modified | 106 |
| Graham | 246 |
| harmonic | |
| adjustable | 113 |
| speed-reducer | 263 |
| triple | 121 |
| Hooke's joint, skewed | 168 |
| hydraulic | 353 |
| hypocycloid, (cycloid), equations for | 443 |
| impulse | 252 319 |
| double | 319 |
| Morse | 252 |
| variable-stroke | 252 |
| zero-max | 252 |
| intermittent, "mutilated tooth" | 108 |
| leadscrew drive | 5 |
| lever and cam | 148 |
| light-duty | 342 |
| linear reciprocator | 117 |
| linkage chain | 153 |
| low-torque | 179 |
| lubricator, Torrington | 258 |
| Lycoming turbine | 273 |
| Maltese cross, double, six-sided | 109 |
| mechanical | 352 |
| missle silo cover | 268 |
| Morse | 252 |
| motor (See Amplifiers) | |
| motor scooter | 240 |
| multicone | 115 |
| multiple disk | 251 |
| ball-and-disk | 251 |
| oil-coated | 251 |
| multiple ratio | 283 |
| nutating-plate (nutation) | 243 |
| offset | 145 |
| | |

| <u>Index Terms</u> | Links |
|--------------------------------|-----------|
| Drives (drivers) cont. | |
| one-way | 314 |
| oscillating | |
| crank and planetary | 118 |
| progressive | 105 |
| parallel | |
| cable | 230 |
| link coupling | 151 |
| plate | 151 |
| pitch | 115 |
| pivot, adjustable | 155 |
| planet, planetary | 106 |
| coupled | 269 |
| triple | 272 |
| | 274 |
| two-gear | 271 |
| simple with inversions | 274 |
| planocentric | |
| pulley | 152 |
| rack and gear, two-directional | 210 |
| ratchet, modified | 96 283 |
| ratios, four, six, and eight | 283 |
| reciprocating-ball | 315 |
| reciprocating-table | 150 |
| redundant torque | 289 |
| ring, double | 248 |
| ring with pulley | 248 |
| rod | 146 |
| shaft, in-line | 287 |
| shift, double | 282 |
| shuttle-gear | 315 |
| shuttle-pinion | 314 |
| slide, elliptical | 171 |
| slide-key | 282 |
| slider, adjustable | 155 |
| sliding change | 282 |
| space crank | 170 |
| space crank, adjustable | 115 |
| speed change, ratchet-tooth | 287 |
| sphere | |
| disk, and | 249 |
| double | 249 |
| roller, and | 249 |
| speed | 318 |
| spherical | 249 |
| ball-and-cone | 250 |
| crank | 167 |
| disk, with | 249 |
| slide oscillator | 168 |
| tilting-ball | 249 |
| swivel-gear | 282 |
| tension controlling | 352 |
| three-dimensional | |
| | 167 |
| three-dimensional crank-slide | 169 |

| Index Terms | Link | s. |
|---------------------------------------|--------|----------------|
| Drives (drivers) cont. | Link | <u>s</u> |
| three gear | 119 | |
| toggle-and-cord | 149 | |
| triple -shaft | 283 | |
| Twinworm, gear | 287 | |
| typewriter | 153 | |
| unidirectional | 253 3 | 20 |
| universal, joint | 169 | |
| valve | 141 | |
| variable-speed, mechanical | | |
| belt-and-chain | 224 | |
| friction | 256 | |
| general | 224 24 | 15 254 256 258 |
| and transmissions | 258 | |
| variable-stroke | 252 | |
| wheel and slider | 121 | |
| Whitworth quick-return | 121 | |
| worm | 5 10 |)9 |
| zero-max | 252 | |
| | | |
| Electromagnetic force | 476 | |
| Electromagnets | 391 | |
| Electron microscope, scanning, (SEM) | 478 | |
| Electron microscope, scanning, (SEM), | | |
| MEMS, images from | 478 | |
| Electrostatic force | 475 4 | /6 |
| Emulation, electronic | 7 | |
| Encoders, (See Sensors, feedback) | | |
| End-effector (See Robots, industrial) | | |
| Epicycloid, (epicyclic) | | 13 481 |
| Epitaxy | 476 | |
| Escapement | | |
| cam-operated | 109 | |
| controlled output | 105 | |
| meter | 109 | |
| ratchet-gear | 109 | |
| solenoid-operated | 109 | |
| Fan | 318 | |
| Fasteners | | |
| hub-to-shaft | 421 | |
| probe-and-socket | 428 | |
| toggle | 407 | |
| Feeders (feeds) | | |
| centerboard selector | 19 | |
| chutes and tubes | 8 | 19 21 |
| long cylinder | 19 | |
| paddle wheel | 19 | |
| parallel·link | 151 | |
| reciprocating | 19 | |
| rotary centerblade | 19 | |
| rotary screw | 19 | |
| vibratory bowl | 25 | |
| | | |

| <u>Index Terms</u> | L | <u>inks</u> | | | | | |
|-----------------------------------|------------|-------------|-----|-----|-----|-----|-----|
| Filter, PM | 388 | | | | | | |
| Fixtures, holding | 424 | | | | | | |
| Fingers, for stopping | 347 | | | | | | |
| Flexspine | 264 | | | | | | |
| Flexures | 183 | | | | | | |
| Flowmeter | 291 | 383 | | | | | |
| Flywheel, malfunction | 261 | | | | | | |
| Focus adjustments | 286 | | | | | | |
| Function generators | 159 | | | | | | |
| Fused deposition modeling (FDM) | | | | | | | |
| (See Rapid prototyping) | | | | | | | |
| 1 1 31 67 | | | | | | | |
| Gages | | | | | | | |
| float | 401 | | | | | | |
| pressure | 148 | 381 | | | | | |
| absolute | 381 | | | | | | |
| Bourdon | 341 | | | | | | |
| differential | 381 | | | | | | |
| strain | 335 | 341 | | | | | |
| Gearheads | 10 | | | | | | |
| right-angle | 10 | | | | | | |
| straight | 10 | 11 | | | | | |
| Gearmotors | 49 | | | | | | |
| Gears (gearing) | | | | | | | |
| hevel | 10 | 11 | 144 | 159 | 243 | 313 | 367 |
| Humpage's | 271 | | | 10) | | 010 | |
| spiral | 10 | 292 | | | | | |
| straddle-design of | 292 | -/- | | | | | |
| Cardan | 140 | 141 | | | | | |
| circular | 97 | 1 11 | | | | | |
| classification | 242 | | | | | | |
| combining | 290 | | | | | | |
| compliant | 289 | | | | | | |
| computer emulation of | 4 | | | | | | |
| cycloid | 99 | | | | | | |
| design of spiral beval and hypoid | 292 | | | | | | |
| differential | 364 | | | | | | |
| direction changing | 143 | | | | | | |
| eccentric | 278 | | | | | | |
| elliptical | 97 | 115 | 275 | 279 | 121 | | |
| epicyclic | 481 | 113 | 213 | 276 | 451 | | |
| external | 243 | | | | | | |
| face | 243 | 290 | | | | | |
| flexible face | 266 | 290 | | | | | |
| harmonic | 263 | | | | | | |
| helical | | 242 | 207 | 214 | | | |
| | 119 243 | 243 | 287 | 314 | | | |
| herringbone | | 202 | | | | | |
| hypoid | 243 | 292 | | | | | |
| hypoid, straddle-design of | 292 | 212 | | | | | |
| idler | 311 | 313 | | | | | |
| indexer, for indexing | 94 | 114 | | | | | |
| indexer with eccentric disk | 94 | | | | | | |
| internal | 243 | | | | | | |

| <u>Index Terms</u> | <u>Links</u> |
|-------------------------------------|----------------------|
| ars (gearing) cont. | |
| lever and sector | 148 |
| miter | 243 |
| noncircular | 275 |
| pinions | 243 |
| pinions | |
| balanced | 10 |
| coupled and racks | 143 |
| planet | 141 |
| sheet-metal cup | 279 |
| spur-gear type | 290 |
| torque-splitting | 367 |
| planet (planetary) | |
| elliptical | 115 |
| general | 99 106 112 239 263 |
| general, cont. | 268 290 329 357 |
| , | 432 442 |
| geneva | 103 104 |
| helical | 10 |
| mechanism | 110 |
| odd-shapes | 97 |
| offset | 375 |
| oscillating | 94 |
| segments, matching | 143 |
| simp le | 271 |
| systems | 271 |
| cam-controlled | 125 |
| external | 432 |
| general | 239 268 |
| internal | 432 |
| | 143 |
| rack-and-pinion ratio | 347 |
| | 94 99 112 263 267 28 |
| ring | 352 432 443 |
| ring, cont. | 443 444 |
| rolling | |
| sheet-metal | 279 |
| shift arrangements | 282 |
| shifting, (gears and clutched) | 284 |
| sine-function | 278 |
| spiral, logarithmic | 278 |
| spur | 276 289 321 |
| square | 276 |
| straight-line direction change, for | 143 |
| strain-wave | 264 |
| sun | 97 113 141 263 289 |
| sun cont. | 432 442 |
| terminology | |
| tooth | 242 |
| dynamics | 243 |
| torque-splitting | 367 |
| train, epicyclic | 481 |
| | |
| traveling | 313 |

| Index Terms | Τ :: | nks | | | |
|--|-------------|-----|-----|-----|-----|
| Gears (gearing) cont. | <u>1711</u> | IKS | | | |
| wooden-tooth | 263 | | | | |
| worm | 99 | 109 | 244 | 279 | 357 |
| worm with hydrostatic engagement, with | 290 | 10) | 277 | 21) | 331 |
| Generators | 270 | | | | |
| DC | 352 | | | | |
| elliptical cam wave | 264 | | | | |
| function | 159 | 164 | | | |
| Genevas | 137 | 101 | | | |
| coupler-driven | 207 | | | | |
| double with differentials | 205 | | | | |
| drives | 203 | | | | |
| conventional | 82 | 84 | | | |
| double-eccentric | 206 | 0. | | | |
| intermittent | 107 | | | | |
| modified | 106 | | | | |
| twin | 103 | | | | |
| dual-track | 103 | | | | |
| eight-station | 205 | | | | |
| external wheel | -00 | | | | |
| charts for angular | | | | | |
| acceleration | 438 | | | | |
| position | 437 | | | | |
| velocity | 437 | | | | |
| eight-slot | 437 | | | | |
| formulas for | 436 | | | | |
| five-slot | 103 | | | | |
| four-slot | 103 | 104 | 106 | 437 | |
| kinematics data for | 436 | | | | |
| six-slot | 103 | 436 | | | |
| four-bar | 103 | | | | |
| four-station | 205 | | | | |
| groove cam | 103 | | | | |
| internal wheel | | | | | |
| charts for angular | | | | | |
| acceleration | 438 | | | | |
| displacement | 440 | | | | |
| velocity | 441 | | | | |
| eight-slot | 437 | | | | |
| formulas for | 439 | | | | |
| four-slot | 104 | 409 | 439 | | |
| kinematics data for | 439 | | | | |
| six-slot | 440 | | | | |
| slot-crank motion | 439 | | | | |
| locking-arm | 103 | | | | |
| locking-slide | 103 | | | | |
| long-dwell | 104 | | | | |
| modified drives | 106 | | | | |
| modified-motion | 104 | | | | |
| noncircular | 97 | | | | |
| oscillating output | 92 | | | | |
| planetary-gear | 81 | | | | |
| rapid-transfer | 104 | | | | |
| | | | | | |

| <u>Index Terms</u> | <u>L</u> i | <u>inks</u> | | | |
|---------------------------------------|------------|-------------|-----|-----|-----|
| Genevas cont. | | | | | |
| ring-gear | 103 | | | | |
| spherical | 110 | | | | |
| wheels | 97 | 436 | | | |
| Governors | | | | | |
| auxiliary piston | 362 | | | | |
| centrifugal | 363 | 364 | | | |
| constant-volume | 363 | | | | |
| differential, varying | 363 | | | | |
| electrical | 365 | | | | |
| force-compensated | 362 | | | | |
| hit-and-miss | 362 | | | | |
| hydraulic | 365 | | | | |
| pneumatic | 364 | | | | |
| pressure-actuated | 363 | | | | |
| speed, automatic | 362 | 366 | | | |
| velocity-type | 363 | | | | |
| Grapple, automatic | 407 | | | | |
| Gripper, leaf-spring | 424 | | | | |
| Gripping System formechanical testing | 426 | | | | |
| Guides, general | 143 | | | | |
| Guides, linear, single -axis | | | | | |
| air-bearing | 5 | | | | |
| ballscrew-driven, (actuated) | 2 | 3 | 12 | | |
| belt-driven | 2 | 12 | | | |
| direction change, for | 143 | 12 | | | |
| hydrostatic | 5 | | | | |
| leadscrew-driven | 2 | | | | |
| magnetic levitation (Maglev) | 5 | | | | |
| nested | 135 | | | | |
| | 133 | | | | |
| rolling elements, circulating or | _ | | | | |
| noncirculating | 5 | | | | |
| sliding, friction contact | 5 | | | | |
| Hall-effect Device (HED) (See Motors | | | | | |
| commutation) | 200 | | | | |
| Hammers, electrically driven | 390 | | | | |
| Hammers, spring-operated | 391 | 400 | | | |
| Hoist | 355 | 408 | | | |
| Holder, instrument | 388 | | | | |
| Holding fixtures, spring-loaded | 424 | | | | |
| Hook release, emergency | 403 | | | | |
| Hoppers | 19 | 21 | 23 | | |
| Hydraulics | | | | | |
| control system | 220 | 353 | | | |
| cylinders | 318 | 336 | 341 | 376 | 378 |
| drives | 353 | | | | |
| intensifier, multi-plunger | | | | | |
| motors | 353 | | | | |
| pumps, feed | 82 | 353 | | | |
| receiver | 220 | | | | |
| robot drive, receiver | 22 | | | | |
| sender | 220 | | | | |
| | | | | | |

| <u>Index Terms</u> | <u>Lin</u> | <u>ks</u> | |
|--|------------|-----------|-----------|
| Hydraulics cont. | | | |
| sensors | 365 | | |
| switch, pressure | 378 | | |
| valves | 82 | | |
| winch control | 222 | | |
| Hydrostatic engagement | 290 | | |
| Hypocycloid | 89 | 91 11 | 1 112 140 |
| Indexing (Indexers) | | | |
| belts, timing and four-bar linkage for | 95 | | |
| gears and eccentric disk for | 94 | | |
| general | 175 | | |
| plunger-actuated | 114 | | |
| quick | 94 | | |
| single-tooth | 92 | 114 | |
| smooth | 95 | | |
| star wheel | 100 | | |
| Indicators | | | |
| automotive, dashboard | 393 | 400 | |
| bellows-actuated | 400 | | |
| bimetallic | 401 | | |
| diaphragm-actiuated | 400 | | |
| liquid level, automotive | 400 | | |
| liquid level with controller | 400 | | |
| motion | 348 | | |
| power | 348 | | |
| pressure | | 349 40 | 1 |
| primary | 348 | | |
| secondary | 348 | | |
| speed and tension | 350 | | |
| temperature | | 349 | |
| Inductosysns (See sensors feedback) | | ., | |
| Input/output (I/O)ports | 7 | | |
| Instruments, recording and controlling | 397 | | |
| Integrated circuits, CMOS | 482 | | |
| Integrated microelectromechanical | 102 | | |
| systems (IMEMS) | 482 | | |
| Interference, electromagnetic, (EMI) | 7 | | |
| interference, erectromagnetic, (EMI) | , | | |
| Jaws, cam-locked | 411 | | |
| Jaws, robot | 38 | | |
| Joints | | | |
| ball | 308 | | |
| ball-and-socket | 301 | | |
| Bendix-Weiss | 331 | | |
| cam | 163 | | |
| captive, passive | 427 | | |
| constant-velocity | 330 | | |
| cylinder | 166 | | |
| cylinder-plane | 166 | | |
| grooved-sphere | 330 | | |
| helix | 166 | | |
| Hooke's, skewed | | 301 33 | C |
| | 100 | -01 00 | - |

| Index Terms | <u>L</u> | <u>inks</u> | | |
|--|----------|-------------|-----|-----|
| Joints cont. | | | | |
| plane | 166 | | | |
| prism | 166 | | | |
| revolute | 166 | | | |
| robot | 43 | | | |
| rotary | 163 | | | |
| rotary, geared, electromechanical | 329 | | | |
| Rzeppa | 301 | 331 | | |
| sliding | 163 | | | |
| sphere | | | | |
| groove | 166 | | | |
| grooved helix | 166 | | | |
| plane | 166 | | | |
| slotted cylinder | 166 | | | |
| slotted helix | 166 | | | |
| torus | 166 | | | |
| torus, helix | 166 | | | |
| True-speed | 301 | | | |
| universal | 183 | 169 | 294 | 301 |
| constant-speed | 301 | | | |
| Keys | 344 | 420 | | |
| Kinematics | | | | |
| external geneva wheel | 436 | | | |
| internal geneva wheel | 439 | | | |
| for planar manipulation | 43 | | | |
| Knee-joint tester | 445 | | | |
| Laminated-object manufacturing (LOM) (See Rapid Prototyping) | | | | |
| Lasers | | | | |
| carbon dioxide IR emitting | 470 | 471 | | |
| helium-neon UV emitting | 468 | | | |
| interferometer, for closed-loop feedback | 6 | 8 | 22 | 27 |
| neodymium YAG | 473 | | | |
| Latches | | | | |
| cam-guided | 213 | | | |
| cocking with lever for | 213 | | | |
| locking | 211 | | | |
| perpendicular-force | 409 | | | |
| re motely controlled | 406 | | | |
| sleeve | 213 | | | |
| Leadscrew positioning | 131 | | | |
| Lever systems | 149 | | | |
| LIGA process (techniques) | 476 | 484 | | |
| Limiters | | | | |
| friction-clutch torque | 343 | | | |
| overloading prevention, for | 343 | | | |
| shear pin | 343 | | | |
| torque, protection | 342 | | | |
| shaft rotation | 346 | | | |
| Linear guides (See Guides single-axis) | | | | |
| Linear resonator | 476 | | | |
| | | | | |

| Index Terms | Li | ink <u>s</u> |
|---|----------|-----------------|
| Linear variable differential transformers | <u> </u> | anks |
| (LVDTs) (See Sensors feedback) | | |
| Linkage, links | | |
| accelerating /decelerating linear strokes | 146 | |
| articulating | 300 | |
| closed-loop | 43 | |
| crank and rocker | 430 | 445 |
| Daniel's | 133 | |
| D-curve | 139 | |
| D-drive | 137 | |
| differential | 163 | |
| door-check | 212 | |
| drag | 431 | |
| eight-bar | 150 | |
| Evans' | 133 | 136 |
| five-bar | 432 | 130 |
| four-bar | 132 | |
| general | 95 | 137 167 212 430 |
| general cont. | 432 | 445 456 |
| industrial applications of | 430 | 113 130 |
| parallel crank | 430 | |
| sliding member, with | 430 | |
| hinged | 300 | |
| hypocyclic-drive | 300 | |
| inventors of | | |
| Daniel | 132 | |
| Evans | 132 | |
| Isoceles | 138 | |
| Peaucellier | 137 | |
| Roberts | 132 | |
| Scott-Russell | 132 | |
| Tchebicheff | 132 | |
| Walschaert | 138 | |
| Watt, James | 132 | |
| Isosceles | 138 | 430 |
| linear force | 186 | |
| linear strokes, accelerating and | 100 | |
| decelerating, for | 146 | |
| long-kick | 133 | |
| motions for | 100 | |
| direction change | 142 | 430 |
| multiplying short | 148 | |
| other | 139 | |
| sliding | 431 | |
| slow | 430 | |
| straight-line, for | 132 | 136 |
| nonparallel equal crank | 430 | 130 |
| offset shaft | 295 | |
| pantograph | 138 | |
| parallellink feeder | 151 | |
| parallelogram | 151 | |
| Peaucellier's | 137 | 431 |
| ratios for straight-line mechanisms | 138 | ·-· |
| 1200 Tot brangite into incommission | 150 | |

| <u>Index Terms</u> | <u>L</u> i | nks | |
|--|------------|-----|-----|
| Linkage, links cont. | | | |
| reciprocating linear force, air spring | 186 | | |
| Roberts' | 138 | | |
| rotary force, air spring | 186 | | |
| rotating crank | 431 | | |
| sacrificing | 218 | | |
| scotch-yoke inversion | 202 | | |
| short-kick | 133 | | |
| spring-type | 190 | | |
| steering actuation for a tractor | 378 | | |
| Tchebicheff's | 138 | 431 | |
| toggle, in different applications for | 123 | 211 | 215 |
| transport mechanisms, for | 65 | | |
| trapezoidal | 430 | | |
| Walschaert's | 138 | | |
| Watt's | 136 | 138 | 430 |
| Watt-Evans' | 133 | | |
| Lock pin, quick-release | 408 | | |
| Machines | | | |
| adhesive applications | 76 | | |
| automatic shear | 89 | | |
| coil-winding | 384 | | |
| cut-off | 399 | | |
| folder or yarder | 89 | | |
| label application | 75 | | |
| loom | 89 | | |
| riveting | 211 | 212 | |
| routing | 223 | | |
| stone-crushing | 211 | | |
| tensile testing | 222 | | |
| winding | 73 | | |
| Magnets, magnetic | | | |
| alnico | 14 | | |
| ceramic | 14 | | |
| clutches | 327 | | |
| designing with permanent | 385 | | |
| detent | 417 | | |
| mechanisms | 387 | | |
| permanent, (PM) | 342 | | |
| rare-earth | 14 | | |
| Manipulators (see Robots industrial) | | | |
| Maltese cross, six-sided | 109 | | |
| Mechanisms | | | |
| adjustable output | 156 | | |
| adjustable stroke | 155 | | |
| adjuster | | | |
| cam-motion | 156 | | |
| linkage-motion | 156 | | |
| piston-stroke | 157 | | |
| valve stroke | 156 | | |
| agitator | 153 | | |
| air-spring | 186 | | |

| <u>Index Terms</u> | <u>Li</u> | <u>ıks</u> |
|---------------------------------------|-----------|------------|
| Mechanisms cont. | | |
| angular motion | 455 | |
| automatic | | |
| feed | 62 | |
| safety for operating machines | 90 | |
| stopping, electrical | 88 | |
| stopping, for faulty machines | 82 | |
| bobbin changer | 86 | |
| cam | | |
| cut-out | 154 | |
| double | 156 | |
| double-faced | 154 | |
| follower motion, fast | 120 | |
| function generator | 164 | |
| ideas for | 207 | |
| sliding | 154 | |
| cam-and-rack | 153 | |
| Cardan-gear | 140 | |
| chain | | |
| adjustable | 155 | |
| oscillating | 118 | |
| slider, and | 118 | |
| clutch | | |
| adjustable | 155 | |
| one-station | 324 | |
| scribing | 151 | |
| two-station | 324 | |
| computing | 159 | |
| counting (counter) | 110 | 340 |
| coupler (coupling) | | |
| four-bar | 206 | |
| link | 329 | 338 |
| special | 337 | |
| crank | 400 | |
| double-parallel | 430 | |
| gear, oscillating | 121 | |
| gear, slider | 121 | |
| nonparallel equal | 431 | |
| parallel | 338 | |
| reciprocating space | 117 | |
| rotating | 431 | |
| crank and rocker, four-bar, design of | 445 | |
| curved-motion cutter | 57 | |
| curve generating | 201 | |
| cutting (cutter) | 56 | |
| clamping and | 56 55 | |
| curved-motion | 57 | |
| four-bar | 56 | |
| parallel | 56 | |
| slicing vertical | 57 57 | |
| | 57 57 | |
| web | 31 | |

| Index Terms | Links |
|--------------------------------|-------|
| Mechanisms cont. | |
| cycloid, cycloidal | |
| curves, family of | 203 |
| equations for the design of | 442 |
| gear | 99 |
| modified | 203 |
| generating | 203 |
| motion | 202 |
| parallelogram | 112 |
| reciprocator | 113 |
| rocker | 112 |
| differential | |
| bevel-gear | 159 |
| general | 159 |
| planetary-gear | 163 |
| rotating-link | 159 |
| sliding-link | 159 |
| differentiator | 162 |
| direction-changing | 142 |
| dwell | |
| cam-helical | 119 |
| cam-roller | 119 |
| cam-worm | 118 |
| double-crank | 119 |
| double, hypocycloid | 111 |
| epicyclic | 118 |
| long | 118 |
| rotary, short | 112 |
| short | 121 |
| six-bar | 119 |
| drive | |
| bearing-and-roller | 117 |
| disk-and-roller | 117 |
| three-gear | 119 |
| long | 118 |
| triple harmonic | 121 |
| Whitworth quick-return | 121 |
| wheel-and-slider | 121 |
| worm | 109 |
| eccentric pivot point | 157 |
| elliptical-motion drive | 113 |
| epicycloid | |
| oscillating-output geneva | 114 |
| plunger-actuated indexer | 114 |
| reciprocator | 113 |
| single-tooth indexer | 114 |
| escapement, electric meter | 109 |
| external geneva | 110 |
| fast-cam follower motion | 120 |
| feed | 52 |
| feeder for curvilinear motions | 456 |
| firing-pin | 214 |
| flipping | 58 |
| | |

| Index Terms | <u>Li</u> | <u>nks</u> | |
|---|------------|------------|-----|
| Mechanisms cont. | | | |
| gear (geared) | | | |
| Cardan | 140 | | |
| five-bar, designing | 432 | | |
| Jensen's ring and slider | 450 | | |
| planetary | 88 | | |
| ring and slider | 450 | | |
| slider | 448 | | |
| generator, function | 159 | 164 | |
| geneva | | | |
| external | 110 | | |
| general | 103 | | |
| internal | 110 | | |
| long-dwell, drive (slotted) | 111 | | |
| spherical | 110 | | |
| guidance, parallel | 83 | | |
| hammer, electrically driven | 390 | | |
| handling, part | 26 | | |
| harmonic drive, adjustable | 113 | | |
| hypocycloid | 89 | 111 | 140 |
| hydraulic cylinder actuated | 376 | | 1.0 |
| indexing (indexer) | 72 | 86 | 94 |
| indexing (indexer) | 108 | 00 | 77 |
| integrator | 162 | 164 | |
| integrator intermittent motion | 97 | 120 | |
| intermittent counter | 110 | 120 | |
| internal geneva | 110 | | |
| leadscrew positioning, triple-ganged | 131 | | |
| lever, double | 431 | | |
| | 409 | | |
| lift-tong | 338 | | |
| link-coupling | 33c 118 | | |
| long-dwell | 133 | | |
| long-kick | 387 | | |
| magnet, permanent (PM) | | | |
| motor, spring | 181 | | |
| oscillating | 117 | 110 | |
| chain | 116 | 118 | |
| crank and planetary | 118 | | |
| output geneva | 114 | | |
| over-centering | 216 | | |
| overriding spring for low-torque drives | 170 | | |
| two-directional override | 179 | | |
| unidirectional override | 179 | | |
| parallel | | | |
| crank | 338 | | |
| cutter | 56 | | |
| guidance | 105 | | |
| link | 150 | | |
| parallelogram, cycloidal | 112 | | |
| parts handling | 52 | | |
| pericycloid | 111 | | |
| permanent magnet | 387 | | |
| pin-and-disk | 122 | | |

| <u>Index Terms</u> | <u>L</u> | inks |
|--|----------|------|
| Mechanisms cont. | | |
| pin-and-disk, sliding | | 123 |
| piston-stroke adjuster | 157 | |
| pivoting | 138 | |
| pivot, point-eccentric | 157 | |
| planar manipulation | 43 | |
| planetary gear | 110 | |
| pneumatic-cylinder actuated | 145 | 376 |
| press, toggle | 212 | |
| pump, rotary | 374 | |
| pulsating planetary, Frudensteins's | 97 | |
| pulse reduction in chain drives, for | 238 | |
| quick-release | 410 | |
| quick-release and positive locking | 410 | |
| rack-and-gear sector | 116 | |
| rack-and-pinion | 38 | |
| reciprocator, reciprocating | | |
| cycloidal | 113 | |
| in-line | 114 | |
| lever | 38 | |
| linear | 117 | |
| rotary to | 114 | |
| track-switching, scotch yoke | 114 | |
| reversing | 158 | |
| ring gear and slider | 450 | |
| ring and slider, Jenson's | 450 | |
| robot | 34 | |
| rocker arm and disk | 123 | |
| roller-dwell | 119 | |
| rotary, short-dwell | 112 | |
| rotary-to-reciprocating motion and dwell | 116 | |
| rotary pump | 374 | |
| rotating crank | 431 | |
| screw | 194 | |
| screw, double-handed | 150 | |
| sector, rack-and-gear | 116 | |
| Sellers' disk | 254 | |
| Shifting, for gears and clutches | 284 | |
| short-dwell | 121 | |
| short-kick | 133 | |
| six-bar dwell | 119 | |
| slicing | 57 | |
| slide, slider | | |
| adjustable | 155 | |
| ballscrew-driven | 3 | |
| crank | 461 | |
| sliding pin and disk | 123 | |
| snap-action | 215 | |
| sort | 52 | |
| sort, feed or weigh | 52 | |
| sorting | 8 | 20 |
| space, four bar | 165 | |
| spherical geneva | 110 | |
| - | | |

| <u>Index Terms</u> | <u>L</u> i | inks |
|---|------------|---------|
| Mechanisms cont. | | |
| spiral and wheel | 110 | |
| springs, flat, in | 174 | |
| stop, simple | 61 | |
| straight-line, linkage ratios for | 138 | |
| straight-line, Watt's | 430 | |
| straight-line | 132 | |
| Roberts' | 431 | |
| stroke-amplifying | 154 | |
| stroke-multiplying | 154 | |
| synchronizer, shaft | 157 | |
| temperature regulating | 396 | |
| tensioning | 150 | |
| tensioning, arm and disk | 123 | |
| tensioning, cycloidal | 112 | |
| thermostatic | 392 | |
| cam | 154 | |
| chain | 118 | |
| four-bar | 116 | |
| single-axis (See Guides, single-axis) | | |
| three-dimensional, (3D) | 156 | 165 |
| three-gear drive | 119 | |
| toggle | | |
| link and disk | 123 | |
| press | 212 | |
| quick-release | 410 | |
| tool changing, robot | 44 | |
| transport | 65 | |
| transversing, for winding machines | 73 | |
| triple pivot | 150 | |
| vibrating | 58 | |
| washing machine | 168 | |
| web cutting | 57 | |
| wedge and disk | 122 | |
| weigh | 52 | |
| weight-regulating | 55 | |
| Microaccelerometers | 475 | 483 |
| Microactuators | 475 | 482 484 |
| Microcontrol systems, integrated (MEMS) | 482 | |
| Microcontrol systems, three-axis inertial | | |
| measurement | 483 | |
| Microelectromechanical systems (MEMS) | 475 | |
| Microelectromechanical systems (MEMS) | | |
| Images, gallery of | 478 | |
| Micrographs, scanning-electron microscope | | |
| (SEM) | 478 | 484 |
| Micro-inertial systems, three-axis | 483 | 484 |
| Micromachines | 475 | 484 |
| Micromachining (fabrication) | | |
| bulk | 477 | |
| multilevel | 478 | |
| surface | 476 | 477 483 |
| Micromechanical actuators | 484 | |
| | | |

| <u>Index Terms</u> | <u>L</u> | <u>inks</u> | |
|--|----------|-------------|---|
| Microminiature, (micro-) | | | |
| flow sensors | 476 | | |
| fuel injectors | 475 | | |
| gear-reduction drive | 481 | 484 | |
| inertial systems, three-axis | 483 | 484 | |
| inkjet nozzle | 476 | | |
| locks | 482 | | |
| motors | 475 | 484 | |
| motors for microtransmissions | 481 | | |
| optical mirror arrays | 478 | | |
| positioner | 286 | | |
| pressure sensors | 475 | | |
| pumps | 475 | | |
| steam engine | 481 | | |
| transducers | 475 | | |
| transducers, piezoelectric | 477 | | |
| transmissions | | | |
| with gear reduction | 480 | | |
| multispeed, for small motors | 481 | | |
| valves | 475 | 476 | |
| Mold shape deposition manufacturing | .,, | ., . | |
| (MSDM) (See Rapid Prototyping) | | | |
| Motion control | | | |
| incremental | 4 | | |
| motors for (See Motors) | | | |
| point-to-point | 4 | | |
| Motion control cont. | | | |
| sequencing | 4 | | |
| speed (velocity) | 4 | | |
| torque | 4 | | |
| Motion controller, (See Controller, motion) | | | |
| Motion control systems | 2 | | |
| card for | 2 | | |
| classification of | | | |
| closed-loop | 2 | 3 | 8 |
| derivative | 4 | | |
| integral | 4 | | |
| position | 4 | | |
| PID | 4 | | |
| proportional | 4 | | |
| open-loop | 2 | 4 | |
| computer-aided emulation in | 4 | • | |
| electric powered | 2 | | |
| electronic components for | 6 | | |
| feedback sensors for (see Sensors, feedback) | U | | |
| glossary of terms for | 9 | | |
| installation and operation | 8 | | |
| <u>-</u> | d | | |
| interpolation circular | 4 | | |
| | 4 | | |
| contouring | • | 7 | |
| linear | 4 | 7 | |
| mechanical components form | 4 | 13 | |
| microcomputer-controlled X-Y table | 13 | | |

| <u>Index Terms</u> | <u>Li</u> | nks | | |
|--|-----------|-----|-----|----|
| Motion control systems cont. | | | | |
| pick and place X-Y | 13 | | | |
| punch press | 13 | | | |
| X-Y inspection | 13 | | | |
| Motors | | | | |
| AC, rotary | 14 | 21 | | |
| commutation | | | | |
| Hall-effect (HED) | 7 | 16 | 18 | |
| linear servomotor | 18 | | | |
| magnetic | 17 | | | |
| mechanical (brush-type) | 7 | 14 | | |
| sinusoidal | 18 | | | |
| comparison of stepping and servo | 7 | | | |
| conical-rotor for braking or clutching | 310 | | | |
| drivers (See Amplifiers) | | | | |
| DC servomotors, rotary, PM | 11 | 14 | 15 | 19 |
| brushless | 7 | 14 | 16 | |
| brush-type | 7 | 14 | 15 | |
| coil-type armature | 14 | 15 | | |
| cup or shell-type armature | 14 | 15 | | |
| disk-type armature | 14 | 15 | | |
| wound armature | 14 | | | |
| electric | 2 | 14 | 34 | |
| hydraulic | 34 | 353 | | |
| linear, servomotors | 7 | 14 | 17 | |
| advantages of | 19 | | | |
| coil assembly | 19 | | | |
| iron-core | 18 | | | |
| ironless | 18 | | | |
| installation of | 19 | | | |
| hydraulic | 34 | 353 | | |
| microminiature | 475 | 476 | 479 | |
| motion control, for | 7 | 14 | | |
| mount, pivoting | 231 | | | |
| piezoelectric | 45 | | | |
| pneumatic | 34 | | | |
| selection of | 7 | | | |
| selsyn | 353 | | | |
| spring | 181 | | 4.0 | |
| stepper (stepping) | 7 | 14 | 19 | 68 |
| applications for | 20 | | | |
| hybrid | 20 | | | |
| permanent-magnet (PM) | 20 | | | |
| variable reluctance (VR) | 20 | 470 | | |
| wedge, MEMS | 478 | 479 | | |
| Multipliers | 1.50 | | | |
| force and stroke | 152 | | | |
| stroke | 150 | | | |
| three-gear stroke | 116 | | | |
| Oscillators | 4=0 | | | |
| dual-mass, MEMS | 479 | | | |
| wide-angle | 152 | | | |

| <u>Index Terms</u> | $\underline{\mathbf{L}}_{\mathbf{i}}$ | <u>inks</u> |
|--|---------------------------------------|-------------|
| Pantograph | 431 | |
| Pericycloid | 111 | |
| Photosensors | 398 | |
| Piezoelectric | | |
| actuator | 45 | 172 |
| actuator clamp | 45 | |
| actuator rotator | 45 | |
| crystal | 345 | |
| effect | 476 | |
| films | 475 | 477 |
| motors (see Motors, piezoelectric) | 455 | |
| transducer | 477 | |
| Pinions (see Gears) | 102 | |
| Pivots, frictionless-flexure | 183 | |
| Pivots, point-eccentric | 157 | |
| Platform, motion, X-Y-Z | 2 | |
| Plunger, spring | 345 | |
| Pneumatic | 1.45 | 27. |
| cylinder | 145 | 376 |
| direction changer | 145 | |
| dump valve | 216 | |
| power applications | 379 | |
| Positioner, linear micron | 286 | |
| Positioning, leadscrew with three-point gear | 131 | |
| Potentiometer (See Sensors, feedback) Press | | |
| direct-acting air | 186 | |
| punch | 211 | 319 |
| safeguards for | 398 | 31) |
| toggle | 212 | |
| Pressure plate, walking | 309 | |
| Profile, trapezoidal velocity | 3 | |
| Prototyping (See Rapid prototyping (RP)) | 5 | |
| Pulleys | | |
| ball-controlled | 225 | |
| cam-controlled | 225 | |
| general | 229 | 341 |
| spring-loaded variable pitch | 225 | |
| Pumps | | |
| design and operating principles of | 370 | |
| eccentric disk | 374 | |
| flexible-vane | 370 | 374 |
| gear | 374 | |
| gearless | 372 | |
| Hele-Shaw-Beacham | 375 | |
| high pressure | 370 | |
| high vacuum | 373 | |
| high volume | 370 | |
| hydraulic | 371 | |
| intensifier, multi-plunger | 373 | |
| internal screw | 373 | |
| oscillating-arm | 375 | |
| Rameli | 374 | |
| | | |

| <u>Index Terms</u> | <u>Links</u> | |
|--|--------------|-----|
| Pumps cont. | | |
| rotary, rotating | | |
| compressor | 374 | |
| cylinder block | 375 | |
| general | 370 | |
| offset planetary gears in | 375 | |
| positive-displacement | 375 | |
| reciprocating | 375 | |
| Rootes compressor | 374 | |
| self-priming | 373 | |
| squeegee | 372 | |
| stroke control | 99 | |
| three-screw | 374 | |
| worm-type | 296 | |
| Puncher, double-toggle | 153 | |
| Rack, locking | 94 | |
| Rapid Prototyping, (RP) | | |
| ballistic particle manufacturing (BPM) | 468 472 | |
| CAD preparation for | 468 474 | |
| directed light fabrication (DLF) | 468 473 | |
| direct-shell production casting (DSPC) | 468 472 | |
| fused deposition modeling (FDM) | 468 471 | |
| general | 468 | |
| laminated-object manufacturing (LOM) | 468 470 | |
| mold SDM, (MSDM) | 474 | |
| research and development in | 473 | |
| selective laser sintering (SLS) | 468 470 | |
| Rapid Prototyping, (RP) cont. | | |
| shape deposition manufacturing (SDM) | 473 | |
| solid ground curing (SGC) | 468 469 | |
| stereolithography (SL) | 468 | |
| three-dimensional printing (3DP) | 468 472 | |
| Ratchets | | |
| cam-driven | 109 | |
| drive | | 322 |
| friction | 211 | |
| general | 124 | |
| internal | 311 | |
| layout | 460 | |
| sheet-metal | 279 | |
| solenoid-operated | 109 | |
| toothless | 124 | |
| Reciprocators | 127 | |
| cycloidal | 113 | |
| epicycloid | 113 | |
| in-line | 113 | |
| linear | 117 | |
| | 105 | |
| rotating-cam sinusoidal | 105 | |
| | | |
| track-switching scotch yoke | 114 | |
| Recorders | 400 | |
| bubbler type | 400 | |

| <u>Index Terms</u> | <u>Links</u> |
|--|--------------|
| Recorders cont. | |
| float | 401 |
| general | 383 |
| Regulator, nonindicating | 397 |
| Relays | |
| overload | 392 |
| thermostatic | 393 |
| time-delay | 393 |
| Release | |
| emergency hook | 403 |
| Pressure, PM | 388 |
| Reducers | |
| impact | 212 |
| ball-bearing | 260 |
| cammed-gear | 115 |
| four-stage | 266 |
| harmonic -drive | 263 |
| one-way output | 313 |
| two-stage | 266 |
| Resolvers, electromechanical (See also | 200 |
| Sensors, feedback) | |
| Resonator, linear | 476 |
| Reversers | 470 |
| double-link | 158 |
| toggle-link | 158 |
| Watts' modified | 158 |
| Rheostat, shunt-field | 346 |
| Roberts' Law | 459 |
| Robots, industrial | 34 |
| advantages of | 35 |
| all-terrain vehicle | 49 |
| | 36 |
| axes | |
| characteristics of | 35 34 |
| definition of | |
| categories | 36 |
| articulated, revolute or jointed arm | 36 |
| cartesian | 36 |
| cylindrical | 36 |
| polar coordinate, (gun-turret) | 36 |
| vertically jointed | 37 |
| continuous-path | 34 |
| controlled-path | 34 |
| degrees-of-freedom | 34 |
| drives, roller and gear for | 48 |
| end effectors | 36 43 |
| electric-powered | 34 |
| floor-standing | 34 |
| gantry, (overhead configured) | 36 |
| end effectors | 44 |
| finger joints for | 45 |
| floor-standing | 34 |
| grippers, hand-like | 36 38 |
| hydraulic-powered | 34 |
| | |

| <u>Index Terms</u> | Li | inks | | | |
|-------------------------------------|---------|------|----|----|----|
| Robots, industrial cont. | <u></u> | | | | |
| jaws | | | | | |
| piston-operated | 38 | | | | |
| rack and pinion | 38 | | | | |
| reciprocating | 38 | | | | |
| manipulators | | | | | |
| general | 34 | 36 | 43 | | |
| six-degree-of freedom | 34 | 46 | | | |
| two-arm, self reconfigurable | 47 | | | | |
| mechanisms for | | | | | |
| planar manipulation with simplified | | | | | |
| kinematics | 43 | | | | |
| tool-changing | 44 | | | | |
| nonservoed | 34 | | | | |
| pendants | 34 | | | | |
| pick-and-place | 34 | | | | |
| point-to-point | 34 | | | | |
| self-configurable, two-arm | 47 | | | | |
| servoed | 34 | | | | |
| specifications for Fanuc robots | 38 | | | | |
| tool changing for a | 44 | | | | |
| tools | 34 | | | | |
| trends | 35 | | | | |
| unlimited sequence | 34 | | | | |
| wrists | | | | | |
| general | 34 | 36 | | | |
| three-degree-of-freedom | 38 | | | | |
| two-degree-of-freedom | 37 | | | | |
| Rollers | 342 | | | | |
| Rollers, ring latch | 257 | | | | |
| <i>g</i> | | | | | |
| Scotch yoke | 114 | 140 | | | |
| Screws | | | | | |
| arrangements, special | 195 | | | | |
| ball bearing | 130 | | | | |
| devices | 191 | | | | |
| differential | 193 | 196 | | | |
| double-threading/threaded | 193 | | | | |
| mechanisms, applications | 194 | | | | |
| motion translation/transformation | 191 | | | | |
| Seals, force-balanced | 381 | | | | |
| Seals, pressure | 381 | | | | |
| Selective laser sintering. (SLS) | | | | | |
| (See Rapid Prototyping) | | | | | |
| Selectors, parts | 59 | | | | |
| Sensors, feedback | | | | | |
| encoders, rotary, optical | 3 | 8 | 22 | | |
| absolute | 8 | 22 | 23 | | |
| brush-type | 22 | | | | |
| hollow-shaft | 22 | | | | |
| incremental | 8 | 22 | | | |
| linear, optical | 3 | 6 | 8 | 22 | 23 |
| rotary, magnetic | 22 | 24 | | | |
| | | | | | |

| Index Terms | ${f L}_{f i}$ | inks | | | | |
|--|---------------|------|------------|-----|------|-----|
| Sensors, feedback, encoders cont. | | | | | | |
| rotary, optical | 8 | 22 | | | | |
| Inductosyns | 8 | 27 | | | | |
| laser interferometers | 3 | 6 | 8 | 22 | 27 | |
| magnetic | 17 | 24 | | | | |
| potentiometers, precision multiturn | 8 | 22 | 28 | | | |
| resolvers | 8 | 17 | 22 | 24 | | |
| servosystem | 22 | | | | | |
| tachometers | 8 | 22 | 25 | 365 | 389 | |
| transducers, angular displacement, (ADTs) | 22 | 26 | | 505 | 30) | |
| transducers, linear velocity, (LVTs) | 22 | 26 | | | | |
| transformers, linear variable displacement | 22 | 20 | | | | |
| (LVDTs) | 8 | 22 | 26 | | | |
| Sensors, pickup, magnetic | 340 | 22 | 20 | | | |
| Sequencer, compact rotary | 267 | | | | | |
| Servomotors (See Motors) | 207 | | | | | |
| Servosystems, feedback sensors for | 22 | | | | | |
| Shape deposition manufacturing (SDM) | 22 | | | | | |
| (See Rapid Prototyping) | | | | | | |
| | 420 | | | | | |
| Shafts, splined | 420 | | | | | |
| Shafts, tapered Sheaves, cam-controlled | 225 | | | | | |
| | _ | | | | | |
| Sheaves, design of | 225 | | | | | |
| Sleeve, cammed | 344 | | | | | |
| Sleeve, splined | 344 128 | 129 | | | | |
| Slides, ball for linear motion | 126 | 129 | | | | |
| Slides, linear, single-axis (See Guides, | | | | | | |
| Linear, single-axis) Slideblocks | 1.47 | | | | | |
| | 146 | | | | | |
| Solenoids | 21 | | | | | |
| applications for | 31 | | | | | |
| box-frame | 30 | | | | | |
| C-frame | 30 | 50 | <i>(</i> 2 | 100 | 1.45 | 265 |
| general | 29 | 59 | 62 | 123 | 145 | 303 |
| open-frame | 30 | 20 | | | | |
| tubular | 29 | 30 | | | | |
| rotary | 30 | | | | | |
| Solid ground curing (SGC) (See Rapid | | | | | | |
| Prototyping) | 205 | | | | | |
| Space frames | 297 | | | | | |
| Splines | 264 | | | | | |
| circular | 264 | | | | | |
| cylindrical | 418 | | | | | |
| face | 419 | | | | | |
| flex | 264 | | | | | |
| involute-form | 418 | 419 | | | | |
| machine-tool | 418 | | | | | |
| square | 418 | | | | | |
| straight-sided | 418 | | | | | |
| taper-root | 419 | | | | | |
| Sprags | 174 | 307 | 311 | 316 | 318 | 320 |
| Springs | | | | | | |
| air | 186 | 187 | | | | |

| <u>Index Terms</u> | <u>L</u> | <u>inks</u> | | | |
|---|----------|-------------|--------------|------|-------|
| Springs cont. | | | | | |
| applications for | 174 | | | | |
| axial compression | 190 | | | | |
| belleville | 189 | 355 | | | |
| bowed | 217 | | | | |
| cantilever | 190 | 100 | 0.1 . | 2.42 | 2 - 2 |
| coil | 188 | 190 | 317 | 342 | 363 |
| compression | 190 | 404 | | | |
| flat, in mechanisms | 174 | 184 | | | |
| helix, Hunter's | 176 | | | | |
| leaf | 188 | 218 | | | |
| motors | 181 | | | | |
| overriding mechanisms | 179 | | | | |
| pop-up | 176 | | | | |
| ring | 411 | | | | |
| return, in mechanisms | 175 | | | | |
| rubber, molded | 188 | | | | |
| stem, DeHaviland's | 176 | | | | |
| tapered-pitch | 188 | 210 | | | |
| tension | 190 | 218 | | | |
| torque | 190 | | | | |
| torsion | 188 | 190 | | | |
| variable rate from | 188 | | | | |
| vibration control/isolation | 190 | | | | |
| volute, in mechanisms | 173 | | | | |
| Sprockets | 228 | | | | |
| Sprockets, driving and driven | 227 | | | | |
| Sprockets, sheet-metal | 279 | | | | |
| Stages, linear (see Guides) | | | | | |
| Stereolithography, (SL) (See Rapid Prototyping) | | | | | |
| Sterling engine | 432 | | | | |
| SUMMiT process | 478 | 484 | | | |
| Switches | | | | | |
| limit | | | | | |
| actuators | 356 | | | | |
| fail safe | 355 | | | | |
| latching | 357 | | | | |
| linear mechanical | 356 | | | | |
| machinery, in | 358 | | | | |
| rotary cam | 357 | | | | |
| rotary geared | 357 | | | | |
| mercury | 84 | 89 | | | |
| microswitch | 91 | 229 | | | |
| reed | 341 | | | | |
| snap-action | 388 | | | | |
| snap-action, toggle | 453 | | | | |
| toaster | 212 | | | | |
| two-way | 145 | | | | |
| Systems | | | | | |
| ballscrew driven, single-axis motion modular belt-driven | 12 | | | | |
| coaxial-shaft | 224 | | | | |
| double-reduction | 224 | | | | |
| dodole leddelloll | 227 | | | | |

| <u>Index Terms</u> | <u>L</u> | <u>inks</u> | | | |
|---|----------|-------------|-----|-----|-----|
| Systems, belt-driven cont. | | | | | |
| fixed-distance | 224 | | | | |
| variable-distance | 224 | | | | |
| braking, foot-controlled | 378 | | | | |
| carburetor | 393 | | | | |
| clutch-brake | 340 | | | | |
| control (See Control systems) | | | | | |
| closed-loop (See Motion control) | | | | | |
| electric, for motion control | 2 | | | | |
| hydraulic control | 220 | | | | |
| mechanical, for tension and speed control | 348 | | | | |
| microcontrol systems, integrated (MEMS) | 482 | | | | |
| microcontrol systems, three-axis inertial | | | | | |
| measurement | 483 | | | | |
| motion control (See Motion control systems) | | | | | |
| open-loop (See Motion control) | | | | | |
| planetary gear | 239 | 268 | | | |
| servo (See Motion control) | | | | | |
| single-axis motion, modular | 12 | | | | |
| Sterling engine | 432 | | | | |
| X-Y | | | | | |
| inspection | 13 | | | | |
| pick-and-place | 13 | | | | |
| table, microcomputer-controlled | 13 | | | | |
| Table, indexing | 318 | | | | |
| Tachometers, (see Sensors, feedback) | | | | | |
| Telecheric | 35 | | | | |
| Thermal expansion | 475 | 476 | | | |
| Thermometer, recording | 392 | | | | |
| Thermostats | | | | | |
| automobile cooling water | 394 | | | | |
| automatic gas range | 394 | | | | |
| electric range | 394 | | | | |
| Three-dimensional printing (3DP) (See | 371 | | | | |
| Rapid Prototyping) | | | | | |
| Toggles | | | | | |
| linkage | 123 | 180 | 211 | 213 | 216 |
| 6 | 452 | 100 | 211 | 213 | 210 |
| snap-action, (over-centering), design of typical applications for | 453 | | | | |
| ** | 433 | | | | |
| Torque | | | | | |
| control (see Control systems) | 250 | | | | |
| converter, Constantio | 259 | | | | |
| limiters | 342 | | | | |
| splitter, floating pinion | 367 | | | | |
| Transducers (See also, Sensors, feedback) | 100 | | | | |
| pressure | 183 | | | | |
| tension-to pressure | 341 | | | | |
| Transformers (See Sensors, feedback) | | | | | |
| Transmissions | _ | | | | |
| ball-type | 355 | | | | |
| belt, for motor scooter | 240 | | | | |
| Constantino torque converter | 259 | | | | |
| | | | | | |

| <u>Index Terms</u> | <u>Links</u> |
|--------------------------------------|--------------|
| Transmissions cont. | |
| Cruise-O-Matic, 3-speed | 272 |
| Fordomatic, 2-speed | 272 |
| general | 296 |
| Graham | 255 |
| helicopter | 290 |
| Hydramatic, 3 speed | 272 |
| lever | |
| cam, and cord | 148 |
| chain | 149 |
| type | 148 |
| Morse | 259 |
| spiral-feed | 149 |
| Thomas | 259 |
| variable-speed | 258 353 |
| worm-gear | 290 |
| Transmitters, pressure | |
| bellows, gage | 382 |
| Bourdon-tube, absolute | 382 |
| diaphragm, differential | 382 |
| Turnbuckle, short, in-line | 424 |
| Vacuum pickup | 75 |
| Valves | |
| circulating water control | 394 |
| dual flow | 403 |
| pilot, lever-type | 397 |
| Variator, cammed gear speed | 115 |
| Vehicle, all terrain | 49 |
| Velocity profile, trapezoidal, motor | |
| V-grooves | 128 |
| Washers, belleville | 172 |
| Wedges, sawtooth | 426 |
| Wedges, sliding | 145 343 345 |
| Wheels, star | 100 |
| Winch, differential, standard | 219 |
| Winch, Hulse | 219 |
| Worms, sheet-metal | 279 |
| | |